



UPMUSE80 LED

Design by Sandro Santantonio



Collection consisting of ceiling or wall lamps, suspended lamps and table lamps with metal frame and removable, washable elastic fabric covering. Available in several colours and sizes.

Typology: WALL, CEILING LAMP

Ratings

- GU24 LED
- CCT 2700 K, CRI 80
- Diffused light
- Surface installation over holes
- Power supply 120V AC
- Switch mode: on-off
- Dimmable ELV trailing edge phase cut LED bulbs
- Steel frame, painted

Product code composition



Ø 80 cm

Silk stretch fabric

Comp. 84% polyester, 16% elastane

(Spandex) for multicolour MC.

Comp. 80% polyamide, 20% elastane

(Spandex) for other colours.

Weight 170/190 gr/m² for multicolour MC.

Weight 195/215 gr/m² for white BC.

Weight 180/200 gr/m² for other colours.

Light fastness (ISO 105 B02) from 3 to 6

Glow wire 750°C for multicolour MC

Glow wire 850°C for white BC / other colours.

UP

MUSE 80

BC white

XX white metal

LED

GU24 3x15W - included
120Vac
diffused beam - 2700K

AR orange

AZ light blue

BL dark blue

FU fuchsia

GI yellow

RO pink

RS red

VE green

VI violet

MC multicolour

FI flower

ST sticks



DRY LOCATION

LED

CRI80



diminable ELV
TRAILING EDGE
PHASE CUT

4800 lm

107 lm/W

example composition code

UP

MUSE80

VE

XX

LED

Available colours



BC

White



AR
Orange



AZ
Light
blue



BL
Dark
blue



FU
Fuchsia



GI
Yellow



RO
Pink



RS
Red



VE
Green



VI
Violet



MC
Multi
color



FI
Flower



ST
Sticks

CUSTOMER

NOTES

UPMUSE80_ _XXLED

Luminous flux for all built-in LED luminaires is shown at source level.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.