



**US LIAI M 1**

Design by Sara Moroni


Collection consisting of metal suspended lamps.  
Available in several colours and sizes.  
Built-in dimmable LED light source.

Typology: suspended

**Ratings**

- Built in **LED** module
- CCT 3000 K
- optic ~40° beam
- Surface installation over holes
- Supply voltage ~100-240V
- Switch mode: on-off
- Dimmable 0/1-10V

lb 4.8 ft<sup>3</sup> 3.343



Product code composition  
**LIAISON / DRIVER INCLUDED**

| Type | Article  | Arch / Final & sphere finishes | Source                                     |
|------|----------|--------------------------------|--|
| US   | LIAI M 1 | NE black / NE black            | LED 9W - optic ~ 40° beam<br>3000K*, 2700K |
|      |          | NE black / OO matt gold        |  |
|      |          | OO matt gold / NE black        |  |



DRY LOCATION CRI>90 **LED** ~671 lm\* 75 lm/W\* 100-240VAC

example composition code **US LIAI M 1 OO NE LED**

Available colors



NE/NE  
Black/black

OO/NE  
Matt gold  
/black

NE/OO  
Black/ Matt  
gold

Customizable

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

USLIAIM1 \_ \_ \_ \_ LED \_\_\_\_\_

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources.  
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.