

**US LIAI P 8**

Design by Sara Moroni

Collection consisting of metal suspended lamps.
Available in several colours and sizes.
Built-in dimmable LED light source.

Typology: suspended

Ratings


- Built in **LED** module
- CCT 3000 K
- optic ~40° beam
- Surface installation over holes
- Supply voltage ~100-240V
- Switch mode: on-off
- Dimmable 0/1-10V

lb 17.44 ft³ 4.222

Product code composition

LIAISON / DRIVER INCLUDED

| Type | Article | Arch / Final & sphere finishes | Source |
|------|----------|--------------------------------|--|
| US | LIAI P 8 | NE black / NE black | LED 8 x 7.5W - optic ~ 40° beam 3000K*, 2700K |
| | | NE black / OO matt gold | |
| | | OO matt gold / NE black | |



DRY LOCATION CRI>90 **LED** ~5368 lm* 89 lm/W* 100-240VAC

example composition code US LIAI P 8 NE NE LED

Available colors



NE/NE
Black/black



OO/NE
Matt gold
/black



NE/OO
Black/ Matt
gold



Customizable

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

USLIAIP8 _ _ _ _ LED

CUSTOMER _____

NOTES _____

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.