

**UP UL 1 160**  
**UP UL 2 160**  
Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminum.  
Available in several colors and sizes.

Typology: WALL, CEILING LAMP

**Ratings**



- Built in **LED** module
- CCT 3000 K
- Uplight (towards surface)
- Installs over 4 in. octagonal J-box (support independently)
- Power supply 120/277V AC
- Switch mode: on-off
- Dimmable 1-10V LED driver
- Painted aluminum profile 23 x 23 mm
- Opalescent diffuser

h10cm lb 20.28 ft³ 20.12  
h25cm lb 21.16 ft³ 20.12


**Product code composition**

**U-LIGHT / h10 cm or h25 cm ceiling lamp with canopy / DRIVER INCLUDED**

Type	Article	Colours	Version	Source
UP	<b>UL 1 160 LED</b> (h10 cm)	<b>AN</b> anthracite grey	<b>XX</b> standard canopy	LED 125W - diffused beam 3000K
	<b>UL 2 160 LED</b> (h25 cm)	<b>RU</b> rust brown		



available heights



DRY LOCATION

CRI90

120/277VAC



**LED**

11000 lm 88 lm/W

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code | **UP** | **UL2160LED** | **AN** | **XX** |

**Available colors**



**AN**  
Anthracite grey



**RU**  
Rust brown

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

UPUL \_ 160LED \_ \_ XX

\_\_\_\_\_

Luminous flux for all built-in LED luminaires is shown at source level.  
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.