

Acoustic performance U-Light



Axolight

From noise to acoustic comfort, how to do it?


Noise is commonly identified as an unwanted and disturbing sound, for example buzzing (an incomprehensible and continuous hum) from a moving car, a drill, etc.

Acoustic comfort is the psychophysical condition of wellbeing a person finds themselves in when they are in an environment where noise is limited.


The measurement of **Reverberation Time (RT60)**, or the time required for sound to become imperceptible, allows the acoustic comfort to be measured in any given environment: the higher the reverberation time, the greater the perception of sound.

A setting with reflective materials (such as marble, cement, glass etc) and/or irregular geometric shapes will have high Reverberation Time and therefore tend to be noisy.

Noise



Acoustic comfort



Introducing sound-absorbing objects into an environment (objects which can reduce the Reverberation Time), is the way in which acoustic comfort can be reached without making any structural changes to the space itself.

How can the efficiency of an object's sound absorbency be measured?

By measuring the Reverberation Time (RT60) of an enclosed environment both with and without sound-absorbing objects, then taking into account the difference, it is possible to calculate their efficiency.

In order to calculate the Reverberation Time (RT60), the Volume of the enclosed space (V) and the cumulative **Equivalent Sound Absorbing Area (A)** of all the surfaces and objects present in the environment must be known:

$$RT60 = 0,161 \times (V/A)$$

The Equivalent Sound Absorbing Area (A) of each single object (i.e. lamp) takes into account the overall sound-absorbing properties of the materials the object is made of, as well as its size and shape.



To identify the sound-absorbing properties of a single material (not the object in its entirety) it is possible to use the **Sound Absorption Coefficient (α)** whose value can vary from 0, where all incident sound is reflected, to 1, where all incident sound is absorbed. Therefore, if the value of α equals 0,5, 50% of the incident sound on the material's surface is absorbed.

U-Light

Timo Ripatti

from 0,54

to 3,11

**Equivalent Sound
Absorbing Area (A)**

from -5,6%


to -49,6%

**Reduction
of noise**


Average 500÷2.000 Hz




Index



pag. 7-10




pag. 11-13



pag. 15-22

Where we tested our products?

The environment used to measure the sound-absorbing properties the Axolight lamps is shown below:



Room data

L → 8 m

w → 6 m

H → 3,1 m

→ 150 m³


The Reverberation Times of the room, with sounds of varying frequencies emitted from an audio source, were measured, first without acoustic lamps, then with 1, 2 or 3 lamps added at a time.

This is how the reduction of sound in the room was calculated.



SPULA180

Lighting performance per lamp
153 W / 9800 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -25,0% | | | | | | | | |
| | -0,8% | -5,3% | -18,0% | -29,4% | -27,7% | -25,6% | -19,2% | -18,0% | -25,0% |
| 2 lamps | -39,8% | | | | | | | | |
| | -1,5% | -10,0% | -30,5% | -45,4% | -43,4% | -40,8% | -32,2% | -29,1% | -39,8% |
| 3 lamps | -49,6% | | | | | | | | |
| | -2,3% | -14,3% | -39,7% | -55,5% | -53,5% | -50,8% | -41,6% | -36,8% | -49,6% |

Equivalent Sound Absorption Area (A) in m² per lamp


| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,11 | 0,65 | 2,06 | 3,63 | 3,63 | 3,64 | 3,45 | 2,45 | 3,11 |



SPULA160

Lighting performance per lamp

125 W / 8575 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -25,0% | | | | | | | | |
| | -0,8% | -5,3% | -18,0% | -29,4% | -27,7% | -25,6% | -19,2% | -18,0% | -25,0% |
| 2 lamps | -39,8% | | | | | | | | |
| | -1,5% | -10,0% | -30,5% | -45,4% | -43,4% | -40,8% | -32,2% | -29,1% | -39,8% |
| 3 lamps | -49,6% | | | | | | | | |
| | -2,3% | -14,3% | -39,7% | -55,5% | -53,5% | -50,8% | -41,6% | -36,8% | -49,6% |

Equivalent Sound Absorption Area (A) in m² per lamp


| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,11 | 0,65 | 2,06 | 3,63 | 3,63 | 3,64 | 3,45 | 2,45 | 3,11 |



SPULA120

Lighting performance per lamp

86 W / 7354 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -16,3% | | | | | | | | |
| | -0,3% | -2,9% | -11,6% | -18,9% | -18,3% | -16,5% | -12,2% | -11,5% | -16,3% |
| 2 lamps | -27,8% | | | | | | | | |
| | -0,6% | -5,6% | -20,8% | -31,7% | -31,0% | -28,3% | -21,7% | -20,0% | -27,8% |
| 3 lamps | -36,5% | | | | | | | | |
| | -0,9% | -8,2% | -28,2% | -41,1% | -40,3% | -37,2% | -29,3% | -26,5% | -36,5% |


Equivalent Sound Absorption Area (A) in m² per lamp

| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,04 | 0,35 | 1,23 | 2,03 | 2,13 | 2,09 | 2,02 | 1,41 | 1,80 |



SPULA090

Lighting performance per lamp
63 W / 4904 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -9,2% | | | | | | | | |
| | -0,1% | -1,5% | -5,7% | -11,3% | -10,5% | -9,8% | -6,6% | -6,5% | -9,2% |
| 2 lamps | -16,8% | | | | | | | | |
| | -0,2% | -3,0% | -10,9% | -20,3% | -19,0% | -17,8% | -12,5% | -12,0% | -16,8% |
| 3 lamps | -23,1% | | | | | | | | |
| | -0,4% | -4,4% | -15,5% | -27,7% | -26,1% | -24,6% | -17,6% | -16,6% | -23,1% |


Equivalent Sound Absorption Area (A) in m² per lamp

| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,02 | 0,18 | 0,57 | 1,11 | 1,11 | 1,15 | 1,04 | 0,74 | 0,93 |



SPULI160

Lighting performance per lamp
125 W / 8575 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -25,0% | | | | | | | | |
| | -0,8% | -5,3% | -18,0% | -29,4% | -27,7% | -25,6% | -19,2% | -18,0% | -25,0% |
| 2 lamps | -39,8% | | | | | | | | |
| | -1,5% | -10,0% | -30,5% | -45,4% | -43,4% | -40,8% | -32,2% | -29,1% | -39,8% |
| 3 lamps | -49,6% | | | | | | | | |
| | -2,3% | -14,3% | -39,7% | -55,5% | -53,5% | -50,8% | -41,6% | -36,8% | -49,6% |

Equivalent Sound Absorption Area (A) in m² per lamp


| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,11 | 0,65 | 2,06 | 3,63 | 3,63 | 3,64 | 3,45 | 2,45 | 3,11 |



SPULI120

Lighting performance per lamp

86 W / 7354 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -16,3% | | | | | | | | |
| | -0,3% | -2,9% | -11,6% | -18,9% | -18,3% | -16,5% | -12,2% | -11,5% | -16,3% |
| 2 lamps | -27,8% | | | | | | | | |
| | -0,6% | -5,6% | -20,8% | -31,7% | -31,0% | -28,3% | -21,7% | -20,0% | -27,8% |
| 3 lamps | -36,5% | | | | | | | | |
| | -0,9% | -8,2% | -28,2% | -41,1% | -40,3% | -37,2% | -29,3% | -26,5% | -36,5% |

Equivalent Sound Absorption Area (A) in m² per lamp


| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,04 | 0,35 | 1,23 | 2,03 | 2,13 | 2,09 | 2,02 | 1,41 | 1,80 |



SPULI090

Lighting performance per lamp

63 W / 4904 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -9,2% | | | | | | | | |
| | -0,1% | -1,5% | -5,7% | -11,3% | -10,5% | -9,8% | -6,6% | -6,5% | -9,2% |
| 2 lamps | -16,8% | | | | | | | | |
| | -0,2% | -3,0% | -10,9% | -20,3% | -19,0% | -17,8% | -12,5% | -12,0% | -16,8% |
| 3 lamps | -23,1% | | | | | | | | |
| | -0,4% | -4,4% | -15,5% | -27,7% | -26,1% | -24,6% | -17,6% | -16,6% | -23,1% |

Equivalent Sound Absorption Area (A) in m² per lamp

| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,02 | 0,18 | 0,57 | 1,11 | 1,11 | 1,15 | 1,04 | 0,74 | 0,93 |






PLUL2180

Lighting performance per lamp

153 W / 9800 lm → per lamp



Ø 180cm

Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| | | | | | | | | | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -21,1% | | | | | | | | |
| | -0,9% | -5,3% | -14,9% | -24,7% | -23,8% | -20,2% | -14,4% | -14,9% | -21,1% |
| 2 lamps | -34,7% | | | | | | | | |
| | -1,7% | -10,1% | -26,0% | -39,6% | -38,4% | -33,7% | -25,2% | -25,0% | -34,7% |
| 3 lamps | -44,1% | | | | | | | | |
| | -2,6% | -14,4% | -34,5% | -49,6% | -48,3% | -43,2% | -33,6% | -32,3% | -44,1% |

Equivalent Sound Absorption Area (A) in m² per lamp


| | | | | | | | | | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| A | 0,12 | 0,66 | 1,65 | 2,86 | 2,96 | 2,68 | 2,46 | 1,91 | 2,49 |



PLUL1180

Lighting performance per lamp

153 W / 9800 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| | | | | | | | | | |
|---|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
|  | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -21,1% | | | | | | | | |
| | -0,9% | -5,3% | -14,9% | -24,7% | -23,8% | -20,2% | -14,4% | -14,9% | -21,1% |
| 2 lamps | -34,7% | | | | | | | | |
| | -1,7% | -10,1% | -26,0% | -39,6% | -38,4% | -33,7% | -25,2% | -25,0% | -34,7% |
| 3 lamps | -44,1% | | | | | | | | |
| | -2,6% | -14,4% | -34,5% | -49,6% | -48,3% | -43,2% | -33,6% | -32,3% | -44,1% |

Equivalent Sound Absorption Area (A) in m² per lamp


| | | | | | | | | | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| A | 0,12 | 0,66 | 1,65 | 2,86 | 2,96 | 2,68 | 2,46 | 1,91 | 2,49 |



PLUL2160

Lighting performance per lamp

125 W / 8575 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| | | | | | | | | | |
|---|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
|  | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -12,7% | | | | | | | | |
| | -0,3% | -2,4% | -9,0% | -14,5% | -14,5% | -12,6% | -9,0% | -8,9% | -12,7% |
| 2 lamps | -22,4% | | | | | | | | |
| | -0,7% | -4,7% | -16,5% | -25,4% | -25,3% | -22,3% | -16,6% | -15,9% | -22,4% |
| 3 lamps | -30,1% | | | | | | | | |
| | -1,0% | -6,9% | -22,8% | -33,8% | -33,6% | -30,1% | -23,0% | -21,6% | -30,1% |

Equivalent Sound Absorption Area (A) in m² per lamp


| | | | | | | | | | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| A | 0,05 | 0,29 | 0,93 | 1,48 | 1,60 | 1,52 | 1,45 | 1,04 | 1,34 |



PLUL1160

Lighting performance per lamp

125 W / 8575 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -12,7% | | | | | | | | |
| | -0,3% | -2,4% | -9,0% | -14,5% | -14,5% | -12,6% | -9,0% | -8,9% | -12,7% |
| 2 lamps | -22,4% | | | | | | | | |
| | -0,7% | -4,7% | -16,5% | -25,4% | -25,3% | -22,3% | -16,6% | -15,9% | -22,4% |
| 3 lamps | -30,1% | | | | | | | | |
| | -1,0% | -6,9% | -22,8% | -33,8% | -33,6% | -30,1% | -23,0% | -21,6% | -30,1% |

Equivalent Sound Absorption Area (A) in m² per lamp


| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,05 | 0,29 | 0,93 | 1,48 | 1,60 | 1,52 | 1,45 | 1,04 | 1,34 |



PLUL2120

Lighting performance per lamp

86 W / 7354 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -7,3% | | | | | | | | |
| | -0,1% | -1,3% | -4,4% | -9,4% | -8,1% | -7,3% | -4,9% | -5,1% | -7,3% |
| 2 lamps | -13,6% | | | | | | | | |
| | -0,3% | -2,5% | -8,4% | -17,2% | -15,0% | -13,6% | -9,3% | -9,5% | -13,6% |
| 3 lamps | -19,0% | | | | | | | | |
| | -0,4% | -3,7% | -12,1% | -23,8% | -21,0% | -19,2% | -13,3% | -13,3% | -19,0% |

Equivalent Sound Absorption Area (A) in m² per lamp


| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,02 | 0,15 | 0,43 | 0,91 | 0,84 | 0,83 | 0,74 | 0,56 | 0,73 |



PLUL1120

Lighting performance per lamp

86 W / 7354 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|--------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -7,3% | | | | | | | | |
| | -0,1% | -1,3% | -4,4% | -9,4% | -8,1% | -7,3% | -4,9% | -5,1% | -7,3% |
| 2 lamps | -13,6% | | | | | | | | |
| | -0,3% | -2,5% | -8,4% | -17,2% | -15,0% | -13,6% | -9,3% | -9,5% | -13,6% |
| 3 lamps | -19,0% | | | | | | | | |
| | -0,4% | -3,7% | -12,1% | -23,8% | -21,0% | -19,2% | -13,3% | -13,3% | -19,0% |

Equivalent Sound Absorption Area (A) in m² per lamp

| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,02 | 0,15 | 0,43 | 0,91 | 0,84 | 0,83 | 0,74 | 0,56 | 0,73 |



PLUL2090

Lighting performance per lamp

63 W / 4904 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| FREQUENCY | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|-------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -5,6% | | | | | | | | |
| | -0,1% | -0,9% | -3,3% | -7,2% | -6,2% | -5,6% | -3,8% | -3,9% | -5,6% |
| 2 lamps | -10,5% | | | | | | | | |
| | -0,1% | -1,8% | -6,4% | -13,5% | -11,7% | -10,6% | -7,4% | -7,4% | -10,5% |
| 3 lamps | -15,0% | | | | | | | | |
| | -0,2% | -2,7% | -9,3% | -19,0% | -16,6% | -15,1% | -10,7% | -10,5% | -15,0% |

Equivalent Sound Absorption Area (A) in m² per lamp


| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A | 0,01 | 0,11 | 0,32 | 0,68 | 0,63 | 0,63 | 0,58 | 0,42 | 0,54 |



PLUL1090

Lighting performance per lamp

63 W / 4904 lm → per lamp



Acoustic performance

Before

Initial Reverberation Time (RT60) in s

| | | | | | | | | | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| | LOW | | MEDIUM | | | HIGH | | AVERAGE | |
| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| RT60 | 1,69 | 2,05 | 2,56 | 2,75 | 2,53 | 2,27 | 1,65 | 2,21 | 2,61 |


After

Reduction of Reverberation Time (RT60) in %

| | | | | | | | | | |
|---------|--------|-------|-------|--------|--------|--------|--------|--------|--------|
| 1 lamp | -5,6% | | | | | | | | |
| | -0,1% | -0,9% | -3,3% | -7,2% | -6,2% | -5,6% | -3,8% | -3,9% | -5,6% |
| 2 lamps | -10,5% | | | | | | | | |
| | -0,1% | -1,8% | -6,4% | -13,5% | -11,7% | -10,6% | -7,4% | -7,4% | -10,5% |
| 3 lamps | -15,0% | | | | | | | | |
| | -0,2% | -2,7% | -9,3% | -19,0% | -16,6% | -15,1% | -10,7% | -10,5% | -15,0% |

Equivalent Sound Absorption Area (A) in m² per lamp

| | | | | | | | | | |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
| A | 0,01 | 0,11 | 0,32 | 0,68 | 0,63 | 0,63 | 0,58 | 0,42 | 0,54 |



Note