

UP UL 1 160 UP UL 2 160 Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminum.
Available in several colors and sizes.

Typology: WALL, CEILING LAMP

Ratings




- Built in **LED** module
- CCT 3000 K
- Uplight (towards surface)
- Installs over 4 in. octagonal J-box (support independently)
- Power supply 120/277V AC
- Switch mode: on-off
- Dimmable 1-10V LED driver*
- Painted aluminum profile 23 x 23 mm
- Opalescent diffuser

h10cm lb 20.28 ft³ 20.12
h25cm lb 21.16 ft³ 20.12

Product code composition

U-LIGHT / h10 cm or h25 cm ceiling lamp with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
UP	UL 1 160 LED (h10 cm)	AN anthracite grey	XX standard canopy	LED 125W - diffused beam 3000K
	UL 2 160 LED (h25 cm)	RU rust brown		



DRY LOCATION

CRI90

120/277VAC



LED

11000 lm 88 lm/W

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).


example composition code | **UP** | **UL2160LED** | **AN** | **XX** |

* If multiple luminaires are being connected to same dimming circuit please consider that source current from power supply unit (LED driver) is 0.1mA

Available colors



AN
Anthracite
grey



RU
Rust brown

CUSTOMER _____

NOTES _____

UPUL _ 160LED _ _ XX

Luminous flux for all built-in LED luminaires is shown at source level.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.