



UPUL1160 - recessed UPUL2160 - recessed Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminum.
Available in several colors and sizes.

Typology: WALL, CEILING LAMP

Ratings

- Built in **LED** module
- CCT 3000 K
- Uplight (towards surface)
- Remote LED driver(s)
- Installs to ceiling or wall (requires recessed strain relief)
- Power supply 120/277V AC
- Switch mode: on-off
- Dimmable 1-10V LED driver (remote)
- Painted aluminum profile 23 x 23 mm
- Opalescent diffuser

h10cm lb 11.02 ft³ 20.12
h25cm lb 11.90 ft³ 20.12

Product code composition

U-LIGHT / h10 cm or h25 cm recessed ceiling lamp / DRIVER INCLUDED

Type	Article	Colours	Version	Source
UP	UL 1 160 LED (h10 cm)	AN anthracite grey	IN recessed canopy	LED 125W - diffused beam 3000K
	UL 2 160 LED (h25 cm)	RU rust brown		



DRY LOCATION CRI90 120/277VAC




LED 11000 lm 88 lm/W



hole Ø 4,5 cm - 1 3/4" / min depth 10 cm - 3 7/8"

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).


example composition code **UP** **UL1160LED** **RU** **IN**



recessed canopy



available heights



Available colors



AN
Anthracite grey



RU
Rust brown

CUSTOMER _____ NOTES _____

UPUL _ 160LED _ _ IN

Luminous flux for all built-in LED luminaires is shown at source level.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.