

U-Light

Timo Ripatti



Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.

sound absorbing product

COLOURS



anthracite grey



canopy



rust brown



canopy


WALL AND CEILING LAMP VERSION



wall or ceiling details



wall or ceiling lamp canopy version



wall or ceiling lamp recessed version




acoustic performance

UP UL 120 3 7/8" recessed



UP UL 2120 9 7/8" recessed

3 7/8" lb 7.05 ft³ 5.29


9 7/8" lb 7.93 ft³ 5.29



recessed canopy



available heights



3 7/8" height

9 7/8" height

U-LIGHT / 3 7/8" or 9 7/8" recessed ceiling lamp / DRIVER NOT INCLUDED

Type	Article	Colours	Version	Source
UP	UL 120 LED (3 7/8")	AN anthracite grey	IN recessed canopy	LED 74W - diffused beam 3000K*, 2700K 24VDC other CCT options available upon request
	UL 2120 LED (9 7/8")	RU rust brown		



DRY LOCATION

CR190



LED

~7736 lm* 104 lm/W* 24Vdc

hole Ø 1 3/4" / min depth 3 7/8"

ADA COMPATIBLE only for UL120LED

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code **UP UL2120LED AN IN**

Casambi compatible.



KITFAPLUL120IAV sound absorbing option ivory.

Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,02	0,15	0,43	0,91	0,84	0,83	0,74	0,56	0,73

UP UL _ 120 LED _ _ IN

CUSTOMER

NOTES

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.