

# U-Light

Timo Ripatti

Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.



sound absorbing product

COLOURS



anthracite grey



canopy



rust brown



canopy



WALL AND CEILING LAMP VERSION



wall or ceiling details



wall or ceiling lamp canopy version




wall or ceiling lamp recessed version




acoustic performance

UP UL 1 120 3 7/8" canopy  
UP UL 2 120 9 7/8" canopy

3 7/8" lb 14.55 ft³ 6.35  
9 7/8" lb 15.43 ft³ 6.35



standard canopy



available heights



3 7/8" height



9 7/8" height

U-LIGHT / 3 7/8" or 9 7/8" ceiling lamp with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
UP	UL 1 120 LED (3 7/8")	AN anthracite grey	XX standard canopy	LED 86W - diffused beam <b>3000K*, 2700K</b> other CCT options available upon request
	UL 2 120 LED (9 7/8")	RU rust brown		

DRY LOCATION CRI90 **LED** ~7736 lm\* 90 lm/W\* 100-305Vac

ADA COMPATIBLE only for UL1120LED

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code **UP UL1120LED RU XX**

Casambi compatible.



Equivalent Sound Absorption Area (A) in m² per lamp

FREQUENCY	125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ	8000 HZ	125-8000 HZ	500-2000 HZ
A	0,02	0,15	0,43	0,91	0,84	0,83	0,74	0,56	0,73

UP UL \_ 120 LED \_ \_ XX

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.