

# U-Light

Timo Ripatti

Collection consisting of wall, ceiling and suspended lamps in aluminium. Available in two colours and sizes. Built-in LED dimmable light source. Available with sound-absorbing panel option.



sound absorbing product

COLOURS



anthracite grey



canopy



rust brown



canopy

WALL AND CEILING LAMP VERSION



wall or ceiling details



wall or ceiling lamp canopy version




wall or ceiling lamp recessed version



acoustic performance

## US ULI 120

lb 18.07 ft³ 11.65



U-LIGHT / downward lighting only / DRIVER INCLUDED

| Type | Article     | Colours                             | Code End | Source   |
|------|-------------|-------------------------------------|----------|--|
| US   | ULI 120 LED | AN anthracite grey<br>RU rust brown | XX       | LED 86W - diffused beam<br>3000K*, 2700K<br>other CCT options available upon request |

DRY LOCATION
 
 CRI90
 
 dimmable
 
 LED
 ~7736 lm\* 90 lm/W\* 100-305VAc

example composition code US ULI120LED RU XX  
Casambi compatible.

KITFASPUL120AAV sound absorbing  

 KITFASPUL120RAV sound absorbing

Equivalent Sound Absorption Area (A) in m² per lamp

| FREQUENCY | 125 HZ | 250 HZ | 500 HZ | 1000 HZ | 2000 HZ | 4000 HZ | 8000 HZ | 125-8000 HZ | 500-2000 HZ |
|-----------|--------|--------|--------|---------|---------|---------|---------|-------------|-------------|
| A         | 0,04   | 0,35   | 1,23   | 2,03    | 2,13    | 2,09    | 2,02    | 1,41        | 1,80        |

CUSTOMER \_\_\_\_\_ NOTES \_\_\_\_\_

US ULI 120 LED \_\_ XX \_\_\_\_\_

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.