

LEGGERE LE ISTRUZIONI GENERICHE PER L'INSTALLAZIONE DI TUTTI GLI APPARECCHI D'ILLUMINAZIONE.

READ GENERAL INSTRUCTIONS FOR INSTALLING ALL LIGHTS.

BITTE DIE ALLGEMEINE MONTAGEANLEITUNG FÜR ALLE LEUCHTEN LESEN.

LIRE LES INSTRUCTIONS GÉNÉRALES POUR L'INSTALLATION DE TOUS LES APPAREILS D'ÉCLAIRAGE.


LEER LAS INSTRUCCIONES GENERALES PARA LA INSTALACIÓN DE TODOS LOS APARATOS DE ILUMINACIÓN.

ЧИТАЙТЕ ОБЩИЕ ИНСТРУКЦИИ ПО МОНТАЖУ.

PAG. I + II


- Controllare che la superficie d'installazione e le viti che ad essa vengono fissate siano adeguate all'apparecchio e ne supportino il peso.
- Ensure the installation surface and the screws that are fastened onto it are suited to the fixture and withstand its weight.
- Sicherstellen, dass die Installationsoberfläche und die Schrauben, die an ihr befestigt werden, für das Gerät geeignet sind und sein Gewicht aushalten.
- Contrôler que la surface d'installation et les vis qui lui sont fixées soient appropriées à l'appareil et qu'elles sont en mesure d'en supporter le poids.
- Controle que la superficie de instalación y los tornillos fijados a ella sean adecuados para el aparato y soporten el peso.
- Проверить, что поверхность установки и крепежные болты соответствуют прибору и имеют подходящую грузоподъемность

ACPOSES04510N




LED 8,6W - 24Vdc
840lm* source

ACPOSES08210N




LED 16,5W - 24Vdc
1640lm* source

ACPOSES14210N




LED 29,5W - 24Vdc
2867lm* source


ACANGOLO90001




ACCAVINOX0300




ACSATXX01 (1 hole)




ACSATXX02 (2 holes 90°)




ACSATXX03 (2 holes 180°)




ACSATXX04 (3 holes 120°)




ACSATXX05 (4 holes 90°)




ACPIEDINO07XX




ACPIEDINO22XX




ACCANOPYRE001




ACCANOPYTO001



ACCANOPYIN001 (for recessed system)



ACBLOCCACAV01



LED DRIVER



CEDMWC00202

dimming 1-10V 24Vdc
driver max 80W

CEDMWC00203

dimming 1-10V 24Vdc
driver max 100W

CEDMWC00204







dimming DALI 24Vdc
driver max 75W

CEDMWC00205

dimming DALI 24Vdc
driver max 100W

CEDMWC00206

dimming 1-10V 24Vdc
driver max 40W



CABLAGGIO SECONDARIO / SECONDARY SIDE CONNECTION


(Nel caso di accorciamento del cavo vedi/If the cable is shortened see/Falls das Kabel verkürzt werden soll siehe/En cas de raccourcissement du composant câble voir/En el caso de acortamiento del cable vea/

Если кабель укорочен, см. инструкции по подключению: WARNING!)


rispettare la polarità / respect the polarity / die richtige Polarität beachten / respecter la polarité / respetar la polaridad / соблюдать полярность

collegare ad una adeguata alimentazione 24VDC / connect to a suitable 24VDC supply

ACCAVOEL2X001



ACCAVOEL4X001 (TWO CIRCUITS)





ACCANOPYIN001
ACCAVOEL2X001
ACCAVOEL4X001



SE NON VENGONO RISPETTATE LE CORRETTE POLARITÀ DEI CAVI I LED SI DANNEGGIANO IRREPARABILMENTE.
IF YOU DON'T RESPECT THE RIGHT POLARITY OF THE WIRES THE LEDS WILL BE DAMAGED IN UNRECOVERABLE MANNER.
BEI ANSCHLU MIT FALSCHER POLARITÄT WERDEN DIE LED LUECHTMITTEL IRREPARABEL ZERSTÖRT.
SI LE POLARITÉ SERONT PAS RESPECTÉ LE LED SERONT ENDOMMAGÉ DE MANIER PERMANENT.
SI LAS POLARIDADES DE LOS CABLES NO SERAN RESPETADAS LOS LED SERÁN DAÑADOS PERMANENTEMENTE.

СВЕТОДИОДЫ ЧУВСТВИТЕЛЬНЫ К ПОЛЯРНОСТИ ЭЛЕКТРИЧЕСКОГО ТОКА, В СЛУЧАЕ НЕСООБЛЮДЕНИЯ ПОЛЯРНОСТИ СВЕТОДИОДЫ БУДУТ ПОВРЕЖДЕНЫ БЕЗВОЗВРАТНО.

24 VDC



ACCANOPYIN001
ACCAVOEL2X001